

## 1. Introduction:

AX-0282 is a solvent cleaner for all types of non-aqueous waxes and oils used in roller-coating machine.

## 2. Description:

Special blend of hidrocarbures with surfactant character.

## 3. Composition:

Flash point:	>70°C
Density:	Approx. 0.82

The values quoted express the margin for physical properties. The tolerances can be obtained from product specifications.

## 4. Properties:

The product is a solvent of low volatility and odor virtually nil, which is emulsified in water instantaneously.

## 5. Minimum storage capability:

The product may be stored with its container tightly closed in a well-ventilated place at a temperature ranging from +5°C to +35°C. Sealed containers have a service life of 6 months.

## 6. Application:

Used as a solvent and cleaning agent for all types of waxes and oils, non- aqueous, used in leather finishing. The product dissolves easily and emulsifies debris deposited wax cylinders and other application equipment, such as the roll coating machine.

Unlike other highly dangerous and volatile solvents such as, p. ej. toluene or xylene, the AX-0282 is very little volatile, is free from aromatics and has excellent self-emulsifying properties, which makes it better suited than most conventional organic solvents.

To clean the roll-coating machine, the product is placed in a container from which the pump sucks the machine falling on the rollers. These are rubbed to remove the remains that are embedded in the cells or grooves of the roller and then rinse with water. It is recommended to collect the waste product as it can be used once or twice more depending on the dirt extracted.

## 7. Safety:

When handling this product the instructions set out in the safety data leaflet must be observed. The relevant safety and precautionary measures for hygiene in the workplace must also be followed when working with chemical products.

## 8. Observations:

The instructions given in this publication are based on the current stand of our knowledge and experience. This does not presuppose any judicial guarantee concerning certain properties nor their suitability for any application in particular. Given the many influences that may occur during the handling and use of our products, the persons handling or transforming them are not exempt from carrying out their own controls or tests. All those receiving our products will be responsible for observing all existing patent rights as well as all current laws and regulations.