

1. Introduction:

Auxiliary for the leather industry.

2. Presentación:

The Compact CT-0536 is an acrylic-butadien copolymer in aqueous solution.

3. Chemical-physical characteristics:

Acrylic-butadiene copolymer in aqueous solution.

Appearance:	Milky liquid.
Solids:	Approx. 18.5%
PH (1:10):	Approx. 7.0
Viscosity:	<500 cP 2/LVT/60
Specific Gravity: at 25°C:	1.015 gr./cm ³

4. Properties:

It is a very compact binder with filler properties, providing smooth finishes with natural feel and look. Good technical characteristics for finished leather for garments.

5. Storage capacity:

The product may be stored with its container tightly closed in a well-ventilated place at a temperature ranging from +5°C to +35°C. Sealed containers have a service life of 12 months.

6. Usage:

For base coat nappa leather finishes medium to low quality leathers for footwear and garment. It can be used as a single product in the finish, along with pigments (and dye, if necessary) and water. It can also be used in any mix of the base coat.

7. Safety:

When handling this product the instructions set out in the safety data leaflet must be observed. The relevant safety and precautionary measures for hygiene in the workplace must also be followed when working with chemical products.

8. Observations:

The instructions given in this publication are based on the current stand of our knowledge and experience. This does not presuppose any judicial guarantee concerning certain properties nor their suitability for any application in particular. Given the many influences that may occur during the handling and use of our products, the persons handling or transforming them are not exempt from carrying out their own controls or tests. All those receiving our products will be responsible for observing all existing patent rights as well as all current laws and regulations.