

# LA-White TC

## 1. Introduction:

Aqueous emulsion of a mixed cellulose ester pigmented with titanium dioxide and free of nitro groups.

## 2. Description:

Aqueous emulsion of a mixed cellulose ester pigmented with titanium dioxide and free of nitro groups.

## 3. Composition:

Solid content:	19-21%
Specific weight:	approx. 1.00 +/- 0.03 g/cm <sup>3</sup>
Viscosity:	approx. 500 to 1,500 cps.
Film:	Smooth, dry and flexible.

## 4. Properties:

LA-White TC is a white lacquer-emulsion used in aqueous finishes as a final or intermediate season.

## 5. Minimum storage capability:

The product may be stored with its container tightly closed in a well-ventilated place at a temperature ranging from +5°C to +35°C. Sealed containers have a service life of 6 months.

## 6. Application:

When handling this product the instructions set out in the safety data sheet must be observed. The relevant safety and precautionary measures for hygiene in the workplace must also be followed when working with chemical products.

## 7. Safety:

When handling this product the instructions set out in the safety data leaflet must be observed. The relevant safety and precautionary measures for hygiene in the workplace must also be followed when working with chemical products.

## 8. Observations:

The instructions given in this publication are based on the current stand of our knowledge and experience. This does not presuppose any judicial guarantee concerning certain properties nor their suitability for any application in particular. Given the many influences that may occur during the handling and use of our products, the persons handling or transforming them are not exempt from carrying out their own controls or tests. All those receiving our products will be responsible for observing all existing patent rights as well as all current laws and regulations.

Update: 25.01.23

Finishing

Water Lacquers

More info

[quimicainternacional.com](http://quimicainternacional.com)