

Helpa Nofoam

1. Description:

Auxiliary product for leather finishing.

2. Presentation:

Anti-foaming agent.

3. Composition:

Watery silicone emulsion.

Appearance:	Viscous liquid.
Nature:	Dispersible in water.
Solids content:	8,5±0,5
pH value (1:10):	7,0±0,5
Colour:	White.
Silicone content:	6,0±0,5

4. Properties:

All purpose anti-foaming agent. Suitable for effluents that contain high surfactant concentrations which cause high foam levels. It can be sprayed at specific times or areas.

5. Minimum storage capacity:

The product can be stored in its well closed container in a well ventilated place at temperatures between +5° and +35°C. In its sealed container it lasts 12 months.

6. Application:

The product must be shaken before its use. The amount to be applied will depend on foam's quantity and quality. Usually it is applied at concentrations between 5 and 150 mg/kg of the medium to be de-foamed, although its addition can be corrected by pre-diluting, if required, in cold water and a soft shake.

7. Safety:

When handling this product the instructions set out in the safety data leaflet must be observed. The relevant safety and precautionary measures for hygiene in the workplace must also be followed when working with chemical products.

8. Observations:

The instructions given in this publication are based on the current stand of our knowledge and experience. This does not presuppose any judicial guarantee concerning certain properties nor their suitability for any application in particular. Given the many influences that may occur during the handling and use of our products, the persons handling or transforming them are not exempt from carrying out their own controls or tests. All those receiving our products will be responsible for observing all existing patent rights as well as all current laws and regulations.

Update: 12.09.14

Beamhouse
and Wet

Other
Auxiliaries