

Tanqin DC/SF

1. Introduction:

Product for leather retanning.

2. Description:

Retanning agent for all kinds of leathers.

3. Composition:

Combination of phenosulphonic based products and formaldehyde free amino-based resins.

Appearance:	Powderish.
Solids content:	>85%
pH value (1:10):	7,50±1
Colour:	Beige.

4. Properties:

It improves the filling and fullness of the hides, especially over the emptiest areas. It improves the grain's firmness by providing it with a soft touch. Furthermore, when using this product for suede split manufacturing, a short plush is obtained and, due to the special filling over the belly areas, the plush is more regular all across the flesh split. Its use over upholstery leathers helps getting milled leathers with regular grain.

5. Minimum storage capability:

This product can be stored in its well closed container, at a well ventilated place, and at temperatures between +5°C and +35°C. Inside its sealed container, this product lasts 12 months.

6. Application:

Even if this product can be used at the main retanning procedure, in case of items to be buffed off, such as nubuk or suede split leathers, it is adviced to use them after fatliquoring and before the final fixation stages.

Safety:

When handling this product the instructions set out in the safety data leaflet must be observed. The relevant safety and precautionary measures for hygiene in the workplace must also be followed when working with chemical products.

8. Observations:

The instructions given in this publication are based on the current stand of our knowledge and experience. This does not presuppose any judicial guarantee concerning certain properties nor their suitability for any application in particular. Given the many influences that may occur during the handling and use of our products, the persons handling or transforming them are not exempt from carrying out their own controls or tests. All those receiving our products will be responsible for observing all existing patent rights as well as all current laws and regulations.

Update: 04.07.16
Beamhouse
and Wet

Resinic retanning agents

More info