

## 1. Introduction:

Auxiliary for the leather industry.

## 2. Presentación:

Acrylic copolymer in aqueous emulsion.

## 3. Chemical-physical characteristics:

Appearance:	Milky liquid.
Solids content:	40 +/-1
PH (1:10):	8.0 to 9.0
Color:	Yellowish.

## 4. Properties:

The RA-1211 is a fine particle binder, with good mechanical stability. It is an universal application resin to any item with good fastness to water. The RA-1211 forms a dry film, transparent and elastic. In addition to its good resistance, the RA-1211 is characterized by a high filling capacity and flexibility without unduly increasing the skin's natural break.

## 5. Storage capacity:

The product may be stored with its container tightly closed in a well-ventilated place at a temperature ranging from +5°C to +35°C. Sealed containers have a service life of 12 months. Sensitive to cold. Protect from frost.

## 6. Usage:

The Bond RA-1211 is ideal for finishing leather posed great demands for water resistance, such as washable leather, eg, polyurethane dispersions for thermoplastic finishes for shoe upper leather and corrected grain. The RA-1211 is particularly useful also for the impregnation of leather to chrome corrected grain and split. Impregnated leathers have a good seal and optimum correction of the grain. The product should be shaken before use.

## 7. Safety:

When handling this product the instructions set out in the safety data leaflet must be observed. The relevant safety and precautionary measures for hygiene in the workplace must also be followed when working with chemical products.

## 8. Observations:

The instructions given in this publication are based on the current stand of our knowledge and experience. This does not presuppose any judicial guarantee concerning certain properties nor their suitability for any application in particular. Given the many influences that may occur during the handling and use of our products, the persons handling or transforming them are not exempt from carrying out their own controls or tests. All those receiving our products will be responsible for observing all existing patent rights as well as all current laws and regulations.

Update: 02.10.17

Finishing

Acrylic  
Resins