

1. Introduction:

This product provides permanent greased and wet touches.

2. Description:

Modified fatty acid esters.

3. Composition:

Appearance:	Pasty liquid
Active substance content:	Approx. 100%
Viscosity (23°C):	Approx. 1500 mPa.s
Color:	Amber.

4. Properties:

AC-0153 improves the fastness of non-waterproofed leather, while preserving at the same time its softness and natural character, giving it a permanent wet greasy feel. On the flesh side there is only a very slight migration. A clear pull-up effect (greasy and aged appearance) of medium grade is obtained. Easy finishing of the leathers treated with this oil. In hydrophobic leathers treated with AC-0153, a high permeability to water vapor is obtained and these leathers can be pumped or polished without this affecting their waterproofing. The results of the Maeser test or the Bally penetrometers usually remain unchanged or even improve with the application of the product. It provides a permanent wet greasy touch.

5. Minimum storage capability:

The product may be stored with its container tightly closed in a well-ventilated place at a temperature ranging from +5°C to +35°C. Sealed containers have a service life of 6 months.

6. Application:

AC-0153 is a product indicated for finishing different leather articles, such as shoeuppers, leathers for leather goods, nubucks, and even leather for upholstery. To obtain the desired effect, usually one or two layers of 5-8 gr. each one per square foot are enough. The application must be done with the roller machine at a roller temperature between 70°C and 80°C.

7. Safety:

When handling this product the instructions set out in the safety data leaflet must be observed. The relevant safety and precautionary measures for hygiene in the workplace must also be followed when working with chemical products.

8. Observations:

The instructions given in this publication are based on the current stand of our knowledge and experience. This does not presuppose any judicial guarantee concerning certain properties nor their suitability for any application in particular. Given the many influences that may occur during the handling and use of our products, the persons handling or transforming them are not exempt from carrying out their own controls or tests. All those receiving our products will be responsible for observing all existing patent rights as well as all current laws and regulations.

Update: 14.10.21

Products for
waterproofing

Auxiliary
finishing
products for
the waterproof
process