

1. Introduction:

AX-0215 is a fluorocarbon polymer in organic solution. Oil and water repellent.

2. Description:

Fluorocarbon polymer in organic solution.

3. Composition:

Appearance:	Transparent liquid.
Flash point:	<21 °C

4. Properties:

Special product in organic solution based on modified fluorocarbon resins. AX-0215 provides hydro and oil repellency properties to the substrate on which it is applied, suitably treated.

5. Minimum storage capability:

The product may be stored with its container tightly closed in a well-ventilated place at a temperature ranging from +5°C to +35°C. Sealed containers have a service life of 6 months.

6. Application:

The product must be shaken before use.

It is normally diluted in mixtures of organic solvents such as ketones, esters and chlorinated solvents. The use of solvents provides better regulation of subsequent penetration. One of the main applications is as a penetration regulator of the undercoats in nappalan finishes.

7. Safety:

When handling this product the instructions set out in the safety data leaflet must be observed. The relevant safety and precautionary measures for hygiene in the workplace must also be followed when working with chemical products.

8. Observations:

The instructions given in this publication are based on the current stand of our knowledge and experience. This does not presuppose any judicial guarantee concerning certain properties nor their suitability for any application in particular. Given the many influences that may occur during the handling and use of our products, the persons handling or transforming them are not exempt from carrying out their own controls or tests. All those receiving our products will be responsible for observing all existing patent rights as well as all current laws and regulations.

Update: 14.10.21

Products for
waterproofing

Auxiliary
finishing
products for
the waterproof
process