

## 1. Introduction:

Waterproofing agent.

## 2. Description:

Waterproofing agent.

## 3. Composition:

Combination of a mixture of silicone-based hydrophobic synthetic fatliquors and special emulsifiers.

Appearance:	Liquid.
Character:	Anionic.
Active matter:	>60%
pH value (1:10):	9.0±1
Colour:	Milky.

## 4. Properties:

Water repellent agent for all skin types with a medium/high degree of water resistance. Suitable for skins that are going to be tested with the Bally penetrometer. Does not contribute to AOX in wastewater. Solvent free. Light and heat resistant.

## 5. Minimum storage capability:

The product may be stored with its container tightly closed in a well-ventilated place at a temperature ranging from +5°C to +35°C. Sealed containers have a service life of 6 months.

## 6. Application:

Either before the main retanning or during the main fatliquoring, it can be applied as normal and in amounts ranging between 2.0% and 4.0%. It must be taken into account that it gives softness to the skin.

## 7. Safety:

When handling this product the instructions set out in the safety data leaflet must be observed. The relevant safety and precautionary measures for hygiene in the workplace must also be followed when working with chemical products.

## 8. Observations:

The instructions given in this publication are based on the current stand of our knowledge and experience. This does not presuppose any judicial guarantee concerning certain properties nor their suitability for any application in particular. Given the many influences that may occur during the handling and use of our products, the persons handling or transforming them are not exempt from carrying out their own controls or tests. All those receiving our products will be responsible for observing all existing patent rights as well as all current laws and regulations.

Update: 21.05.23

Products for  
waterproofing

Main water  
repellent  
products